

SAVOX® ultra-light headsets

SAVOX® E-C speaker unit



User data

- for surveillance and police tasks
- adaptable to both ears
- adapts to all SAVOX PTT units



TECHNICAL DATA

Weight	20 g
Microphone	vibration sensitive
Speaker impedance	according to application
Cable	Ø 2 mm/760 mm
Connector	4-pole quick release plug
Operation temperature	-25 to +63 °C (continuous)
Supply voltage	2,5–10,0 VDC
ESD, EMI immunity	conforms to EN 301 489-1

OPTIONS

- direct models with in-line PTT

SAVOX® G-C ultra-light hands-free ear set



User data

- for surveillance and police tasks
- quick-release connector
- comfortable to wear during sustained operations
- adaptable to both ears
- no blocking of ambient sounds
- light, yet robust
- adapts to all SAVOX PTT units



TECHNICAL DATA

Weight	10 g (excluding push-to-talk/switch unit)
Size	12 x 42 x 100 mm
Microphone	electret, according to application/device

OPTIONS

- direct models with in-line PTT

SAVOX® L-C behind-the-neck headset

IP67



User data

- electret condenser microphone
- windscreen
- ear cushion
- adapts to all SAVOX PTT units



TECHNICAL DATA

Frequency range	100 Hz to 2.5 kHz
Gooseneck	Ø 4 mm
Cable	Ø 3.6 mm
Ingress protection	IP 67

Behind-the-neck headset



User data

- electret condenser microphone
- windscreen
- adapts to all SAVOX PTT units



TECHNICAL DATA

Frequency range	100 Hz to 2.5 kHz
Gooseneck	Ø 2.5 mm
Cable	Ø 2 mm